


DATA SHEET

Lembar data produk



4SPV8-25 T

Submersible Pump



Spesification:

Device application / Aplikasi	- Water Supply from well or reservoirs / Suplai air dari sumur atau tandon air. - Domestic use, for civil and industrial application / Penggunaan domestik, untuk rumah tangga dan industri.
Power / Listrik	4 kW / 5.5 HP (3 Phase : 380 - 415V / 50 Hz)
Outlet	2"
Max. Head / Head Maks.	125m
Max. Flow	8 m³/h
Max. Capacity / Kapasitas Maks.	133 l/min (on H : 85 m)
Max. Fluid temperature / Temperatur Cairan Maks.	Up to +50°
Max. Sand Content / Kandungan Pasir Maks.	0.25 %
Min. Well Diameter / Diameter Sumur Min.	4"
Construction Material / Material Komponen	- Delivery Casing : AISI 304 SS - Suction Latern : AISI 304 SS - Diffuser : AISI 304 SS - Impeller : AISI 304 SS - Shaft : AISI 304 SS - Shaft Coupling : AISI 304 SS - Wear ring : Rubber - Motor external casing : AISI 304 SS - Top Chock : AISI 420 SS - Bottom Support : AISI 304 SS - Mechanical Seal : Special for deep well (Graphite-Ceramic) - Shaft : AISI 304 SS - Seal Lubricant Oil : Oil for food machinery & pharmaceutic use.