


DATA SHEET

Lembar data produk



6SPV30-6 T Submersible Pump



Spesification:

Device application / Aplikasi	- Water Supply from well or reservoirs / Suplai air dari sumur atau tandon air. - Domestic use, for civil and industrial application / Penggunaan domestik, untuk rumah tangga dan industri.
Power / Listrik	5.5 kW / 7.5 HP (3 Phase : 380 - 415V / 50 Hz)
Outlet	3"
Max. Head / Head Maks.	63 m
Max. Flow	42 m³/h
Max. Capacity / Kapasitas Maks.	700 l/min (on H : 24 m)
Max. Fluid temperature / Temperatur Cairan Maks.	Up to +50°
Max. Sand Content / Kandungan Pasir Maks.	0.25 %
Min. Well Diameter / Diameter Sumur Min.	6"
Construction Material / Material Komponen	- Delivery Casing : AISI 304 SS - Suction Latern : AISI 304 SS - Diffuser : AISI 304 SS - Impeller : AISI 304 SS - Shaft : AISI 304 SS - Shaft Coupling : AISI 304 SS - Wear ring : Rubber - Motor external casing : AISI 304 SS - Top Chock : AISI 420 SS - Bottom Support : AISI 304 SS - Mechanical Seal : Special for deep well (Graphite-Ceramic) - Shaft : AISI 304 SS - Seal Lubricant Oil : Oil for food machinery & pharmaceuic use.