DATA SHEET


Lembar data produk



POMPA SEMI-JET
SELF PRIMING

BJZ - Series

Performance curves



Spesification:

Device application / Aplikasi	Water Distribution / Distribusi Air
Power / Listrik	BJZ 037 : 0.37 kW / 0.5 HP BJZ 075 : 0.55 kW / 0.75 HP
Inlet / Outlet	1" x 1"
Max. Suction / Daya hisap Maks.	9 meter
Max. Head / Head Maks.	BJZ 037 : 22 meter BJZ075 : 30 meter
Max. Flow	BJZ 037 : 2.4 m3/h BJZ075 : 3.6 m3/h
Max. Capacity / Kapasitas Maks.	BJZ 037 : 40 ltr/min BJZ075 : 60 ltr / min
Fluid rate temperature / Temperatur Cairan	Up to 50°
Max. ambient temperature / Temperatur Maks.	Up to +50°
Construction Material / Bahan Dasar Pompa	- Pump Body : Stainless Steel+Cast Iron (Motor Body) - Impeller : Stainless Steel
Pump Feature / Fitur Pompa	- Thermal Protector - Protection :Ip55 - Self Priming

Pump Structure

NO.	Name
1	Plug
2	Washer
3	Dust cap
4	Inside hexagonal bolt
5	Pump housing component
6	O-Ring
7	O-Ring
8	Ejector
9	Key
10	Difusser
11	Hexagonal Nut
12	Spring washer
13	Impeller
14	Mechanical seal
15	Pump cover
16	Motor

